



Pneumatic grease pump 50:1

SRL 600, 20-30 kg container

Item number: 18 711 051

EAN:

Discount group: D

technical data

length suction tube:	600
Pressure ratio:	50:1
Max. diameter (mm):	130
Max. air pressure (bar):	10
Min. air pressure (bar):	2
recommended air pressure (bar):	8
cylinder capacity engine cm ³ :	220
cylinder capacity pump cm ³ :	8
quantity of strokes at 8 bar at a free-flow (min.):	220
pump capacity at 8 bar at a free-flow (g/min):	1100
pump pressure at 8 bar air pressure (bar):	400
air consumption at 8 bar air pressure (l/min):	400
length of discharge pipe work:	Depends on size of installation.
Max. suction height:	The pump is constructed to be operated directly at the point of suction
compressed air connection:	G 1/4" female
grease connection suction side (ø mm):	35
grease connection, pressure side:	G 1/4" male
Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A):	78
Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A):	77
viscosity of discharged liquid:	grease up to NLGI 2
classical liquids to be discharged:	lubricating greases
time duration for 1 complete container draining:	50 kg of grease in 50 min.
colour:	blue Pantone 294 c
length of engine (mm):	225
weight engine (kg):	3,400
weight (g):	6,56

specification

- for 20- up to 30-kg-container
- Suction tube
- Special pump mechanism
- Pressure reducing valve (pre-set at 8 bar)
- Male quick release adapter (20 062)
- The pump is designed to be operated for the discharge of lubricating and multi purpose greases NLGI 0 up to NLGI 2 out of original manufacturer's container, i.e. greases for recharging of centralised lubricating systems

notes

- Pump is easy to disassemble for cleaning matters.
- Operate pneumatic grease pump with maintenance unit 20 218 950, only.

packaging



Dimensions LxWxH (mm):	1000 x 170 x 170
Weight (kg):	7,18
Packing unit:	1.0