

FIXED VARNISHED HOSE REELS FOR DIESEL 10 bar



The automatic varnished steel hose reels with spring are suitable to hold flexible hoses for diesel delivery. They allow to unroll only the necessary hose length, improving their functionality.

Equipped with:

- Antistatic black rubber hose 10 bar
- Galvanized connections
- Galvanized swiveling joint 90°
- Viton seals

F-460



Ref.	Flow rate	Hose length	Ø hose	Inlet-Outlet
	l/min	m	G	
070-1308-500	80	without hose	-	F3/4"G-M1"G
070-1308-508	80	8	3/4"	F3/4"G-M1"G

F-550



Ref.	Flow rate	Hose length	Ø hose	Inlet-Outlet
	l/min	m	G	
070-1408-600	95	without hose	-	F1"G - M1"G
070-1408-510	85	10	3/4"	F1"G - M1"G
070-1408-515	85	15	3/4"	F1"G - M1"G
070-1408-610	93	10	1"	F1"G - M1"G

F-555



Ref.	Flow rate	Hose length	Ø hose	Inlet-Outlet
	l/min	m	G	
070-1508-600	95	without hose	-	F1"G - M1"G
070-1508-520	83	20	3/4"	F1"G - M1"G
070-1508-615	90	15	1"	F1"G - M1"G

F-560



Ref.	Flow rate	Hose length	Ø hose	Inlet-Outlet
	l/min	m	G	
070-1608-600	95	without hose	-	F1"G - M1"G
070-1608-530	80	30	3/4"	F1"G - M1"G
070-1608-540	75	40	3/4"	F1"G - M1"G
070-1608-620	87	20	1"	F1"G - M1"G
070-1608-630	85	30	1"	F1"G - M1"G