



### Barrel pump-G 2"-M 64x4

SRL 355-955-24 l/min

**Item number:** 13 044  
**EAN:** 4103810130441  
**Discount group:** A

#### Technical data

**Delivery rate (l/stroke):** 0,4  
**Delivery rate at 60 strokes/min (l/min):** 24  
**Pumping media:** Oils up to SAE 50, diesel, petroleum, kerosene, glycerin and antifreeze undiluted  
**Usage:** Container 60/200/220 l  
**Length, three-part suction pipe (mm):** 355 - 955  
**Barrel screw coupling:** G 2" male and M 64x4 male



#### Materials of parts in contact with liquid

**Pump body:** ABS + PA6  
**Seals:** FKM  
**Metal pieces:** steel, galvanized  
 stainless steel  
 Steel, powder coated

**Weight (kg):** 1,24

#### Specification

- Pump housing with piston, hand lever and discharge spout
- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" (13 085) and barrel screw coupling M 64x4 (13 085 003)
- Discharge hose, 1500 mm, with steel discharge spout (13 044 010)
- Hose holder (00 845)
- Discharge spout (81 112)
- Valuable sales package



#### Special notes

- Constant delivery rate for many years
- Completely dismountable - easy to clean
- Spare parts, seals and pistons available for 10 years
- Simple barrel installation by screw coupling
- Can be freely positioned in 30° increments
- Optional barrel adapters: (13 085 001) barrel adapter S 56x4; (13 085 002) barrel adapter S 69,5x5,5; (13 085 003) barrel adapter M 64x4 male; (13 085 006) barrel adapter S 64x5
- 3 year warranty (excluding wearable parts)
- Suction strainer, (13 097 003), optional for telescopic suction tube (13 094)

#### Packaging

**Dimensions LxWxH (mm):** 395 x 243 x 125  
**Weight (kg):** 2,3  
**Packing unit:** 1,0





