



## Rotary pump

SRL 355-955 mm-18 l/min

**Item number:** 13 055  
**EAN:** 4103810130557  
**Discount group:** A

### Technical data

**Delivery rate (l/rotation):** 0,3  
**Delivery rate at 60 rotations/min (l/min):** 18 (Diesel)  
**Pumping media:** Oils, up to SAE 90, self-lubricating, non-aggressive media, fuel oil, diesel, petroleum  
**Usage:** Container for 60 / 200 / 220 l  
**Application:** For filling measuring vessels, storage cans and canisters  
**Discharge:** Discharge spout  
**Length, three-part suction pipe (mm):** 355 - 955  
**Barrel screw coupling:** G 2" male  
**Material pump housing:** Impact resistant die casting

### Specification

- Telescopic suction tube (13 094), adjustable in length (from 355 to 955 mm)
- With suction filter (13 097 003)
- Barrel screw coupling G 2" (04 464 001)
- Discharge spout (81 112)

### Special notes

- Smooth hand-rotating operation without irretations
- Excellent suction performance due to highest component precision
- Very compact design
- Impact resistant pump housing
- Non-slip handle
- Covering of the different components exclusively trough the seals
- Assembly, commissioning and container change without tools
- Completely dismountable - easy to clean
- Warranty 3 years when using the supplied suction basket (excluding wear parts)

### Packaging

**Packing unit:** 1,0  
**Dimensions LxWxH (mm):** 390 x 120 x 240  
**Weight including package (kg):** 2,85

