



Pneumatic pump 1:1

SRL 860-200/220 I container

Item number: 19 135

EAN:

Discount group: D

technical data

length suction tube:	860
Pressure ratio:	1:1
Max. diameter (mm):	130
Max. air pressure (bar):	10
Min. air pressure (bar):	2
recommended air pressure (bar):	8
cylinder capacity engine cm ³ :	220
cylinder capacity pump cm ³ :	220
quantity of strokes at 8 bar at a free-flow (min.):	240
pump capacity at 8 bar at a free-flow (l/min):	66
pump pressure at 8 bar air pressure (bar):	8
air consumption at 8 bar air pressure (l/min):	450
length of discharge pipe work:	Depends on size of installation.
Max. suction height:	6 m, suction tube G 1"
compressed air connection:	G 1/4" female
oil connection - suction side:	G 1" female
oil connection - delivery side:	G 3/4" male
connection container:	G 2" male, drum adapter
Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A):	78
Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A):	77
viscosity of discharged liquid:	oil up to ISO VG 15 SAE 5
classical liquids to be discharged:	diesel and oil
time duration for 1 complete container draining:	200 l diesel in 3 minutes
colour:	blue Pantone 294 c
length of engine (mm):	375
weight engine (kg):	4,300

specification

- pneumatic oil- and diesel pump 1:1.
- Does not correspond to German calibration law (NEF).
- for 200/220 l container
- Suction tube, G 1" male
- To discharge low viscosity self-lubricating liquids, such as diesel, fuel oil and engine oil
- Due to its high delivery rate, it can be used as a filling pump

notes

- Operate pneumatic-pump with maintaining unit 20 218 950

packaging

Dimensions LxWxH (mm):	1310 x 190 x 195
Weight (kg):	6,850
Packing unit:	1.0