



Pneumatic pump 5:1-DW-NEF

SRL 860-200/220-l-container

Item number: 19 335

EAN:

Discount group: D

Technical data

Length of suction tube (mm): 860 Pressure ratio: 5:1 130 Max. diameter (mm): Max. air pressure (bar): 10 Min. air pressure (bar): 2 Recommended air pressure (bar): 8 Cylinder capacity engine cm³: 220 Cylinder capacity pump cm3: 70 Quantity of strokes at 8 bar at a free-flow

(min.): 270

Pump capacity at 8 bar at a free-flow (I/min): 20
Pump pressure at 8 bar air pressure

bar): 40

Air consumption at 8 bar air pressure

(I/min): 470
Length of discharge pipe work: Depends on size of installation.

Max. suction heighh: 6 m, suction tube G 3/4"

Compressed air connection: G 1/4" female

Oil connection - suction side: G 3/4" female
Oil connection - delivery side: G 1/2" male

Connection container: G 2" male, drum adapter

Noise level idle running acc. to ISO

9614-2 at a distance of 2 m (db A): 78

Noise level under load acc. to ISO

9614-2 at a distance of 2 m (db A): 77

Viscosity of discharged liquid: oil up to SAE 140

Classical liquids to be discharged: engine, gear and hydraulic oil

Time duration for 1 complete container

draining: 200 l oil in 14 minutes Lacquering: blue, Pantone 294 C

Length of engine (mm): 360
Weight of motor (kg): 4

Specification

- Pneumatic oil pump 5:1, double acting (DW)
- Can not be calibrated for public sales (NEF)
- For 200/220 I container
- Suction tube, G 3/4" male
- Double-acting pump, provides a continuous flow of media
- Especially designed for oil supply over long distances
- To discharge engine, gear and hydraulic oils
- Designed for use in conjunction with pipe lines. We strongly recommend the use of an overflow valve ((19 648), 16 bar, or (19 506), 20 bar).
- Can be easily combined with several hose reels

Special notes

• Operate pneumatic pump with maintenance unit (20 218 950)

Packaging

Dimensions LxWxH (mm): 1310 x 190 x 195

Weight (kg): 7,42
Packing unit: 1.0