



PREMx 43 l/min-11.4 gpm

24 V-DC-ABK

Item number: 23 720
EAN: 4048358237200
Discount group: D

Technical data

Connecting cable with battery terminal clips, length (m) / (ft): 2 / 6.6
 Connection container: G 2" male, drum adapter
 Connection suction side: hose fitting DN 19
 Connection discharge side: G 1" male
 Hydraulic data
 Pump design: axial gear
 Delivery rate under free discharge up to (l/min) / (gpm): 43 / 11.4
 Suction height up to (m) / (ft): 2,5 / 8.2
 Discharge height max. (m) / (ft): 15 / 49.2
 Pumping media: fuel oil and diesel
 Motor data
 Voltage (V): 24 V DC
 Power consumption (A): 10
 Power (W): 240
 Thermal protection: self resetting
 Duty cycle (min): 30
 Rotation speed at 0,5 bar counterpressure (rpm): 7500
 Type of construction: IMB 5
 Safety class: IP34
 Material of pump housing and pump: PA 6
 Dimensions LxWxH (mm) / (inch): 130 x 130 x 350 / 5.1 x 5.1 x 13.7
 Weight with accessories (kg) / (lb): 2,5 / 5.5

Specification

- For 200 up to 1000 l container
- Barrel screw coupling, G 2" male
- Siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- Motor with thermal protection switch, self resetting
- Battery terminal clips, 2 m cable
- Illuminated on/off switch
- Valuable sales package

Special notes

- The pump is lightweight and very quiet in operation.
- Resistant against small dirt particles in the liquid to be discharged
- The liquid column is to be established via manual pumping
- Can be manually operated in case of electric power blackout
- Pump can only be utilized as barrel pump
- Replace the carbons when the pump has delivered a volume of 100,000 l

Packaging

Dimensions LxWxH (mm) / (inch): 330 x 260 x 220 / 12.9 x 10.2 x 8.6
 Weight including package (kg) / (lb): 2,7 / 6
 Packing unit: 1,0

