

STAINLESS STEEL AUTOMATIC HOSE REELS AISI 304 FIXED FOR WATER 150 °C 400 bar




Equipped with:

- Synthetic rubber hoses no trace blue 2SC
- Galvanized connections
- Swivelling joint 90° stainless steel AISI 304
- Viton seals



FX-400	Article	Hose length	Ø hose	Inlet-outlet
	070-2205-300	Without hose	-	M3/8"G - M3/8"G
	070-2205-400	Without hose	-	M1/2"G - M1/2"G
	070-2205-210	10 m	5/16"	M3/8"G - F3/8"G
	070-2205-215	15 m	5/16"	M3/8"G - F3/8"G
	070-2205-310	10 m	3/8"	M3/8"G - F3/8"G
	070-2205-410	10 m	1/2"	M1/2"G - F1/2"G
FX-460	070-2305-300	Without hose	-	M3/8"G - M3/8"G
	070-2305-400	Without hose	-	M1/2"G - M1/2"G
	070-2305-220	20 m	5/16"	M3/8"G - F3/8"G
	070-2305-315	15 m	3/8"	M3/8"G - F3/8"G
	070-2305-318	18 m	3/8"	M3/8"G - F3/8"G
	070-2305-415	15 m	1/2"	M1/2"G - F1/2"G
FX-550	070-2405-300	Without hose	-	M3/8"G - M3/8"G
	070-2405-400	Without hose	-	M1/2"G - M1/2"G
	070-2405-320	20 m	3/8"	M3/8"G - F3/8"G
	070-2405-325	25 m	3/8"	M3/8"G - F3/8"G
	070-2405-420	20 m	1/2"	M1/2"G - F1/2"G
FX-555	070-2505-300	Without hose	-	M3/8"G - M3/8"G
	070-2505-400	Without hose	-	M1/2"G - M1/2"G
	070-2505-330	30 m	3/8"	M3/8"G - F3/8"G
	070-2505-425	25 m	1/2"	M1/2"G - F1/2"G
	070-2505-430	30 m	1/2"	M1/2"G - F1/2"G
FX-560	070-2605-400	Without hose	-	M1/2"G - M1/2"G
	070-2605-340	40 m	3/8"	M1/2"G - F3/8"G
	070-2605-440	40 m	1/2"	M1/2"G - F1/2"G

OVERALL DIMENSIONS FIXED

Mod.	A	B	C	D	E	F	G	H			
FX-400	158	120	168	192	95	450	400	435	12,50<19,50	0,046	1
FX-460	158	120	168	192	95	480	460	500	16,50<23,00	0,060	1
FX-550	200	150	225	270	120	590	550	600	22,00<45,00	0,085	1
FX-555	250	200	225	270	170	590	550	600	26,00<53,00	0,100	1
FX-560	440	390	225	270	360	590	550	600	33,00<83,00	0,180	1