



Hose reel-for oil

GDA-WB-120 bar-DN 12-15 m

Item number: 29 173
EAN: 4103810291739
Discount group: D

technical data

length of discharge hose (m): 15
connection discharge hose: G 1/2" male/female
length of connecting hose (m): 1
connection to connecting hose: G 1/2" female/female
inner diameter of hose (DN): 12
operating pressure max. (bar): 120
colour
casing: window grey, satin, RAL 7040
arm: window grey, satin, RAL 7040
supporting plate: window grey, satin, RAL 7040
encasing: Pantone 294c, blue satin
mounting bracket: Pantone 294c, blue satin
Dimensions LxWxH (mm): 495 x 158 x 508
Weight (kg): 26,100

specification

- encased, for wall/floor mounting, outside swivel
- With hose stop

notes

- Pressol hose reels are exceedingly robust and are notable for their compact design.
- All metal parts are phosphatized, undercoated and painted.
- The high quality surface treatment of all steel parts ensures high corrosion resistance
- Axis (Ø 40 mm) of die cast parts. Dimensions selected by our engineers ensure almost unlimited life range
- The material combination axis / bearing and the spring unit are maintenance-free
- Easy assembly because the weight of the hose reel does not need to be supported while mounting.
- All swivel joints are ball bearing based
- High pressure in the supply system does not influence the power needed to rotate the drum.
- The hose can be engaged by rotating 1/4 turn.

packaging

Dimensions LxWxH (mm): 540 x 580 x 160
Weight (kg): 26,900
Packing unit: 1.0