



### Hose reel-for grease

GDA-WB-400 bar-DN 6-10 m

**Item number:** 29 272  
**EAN:** 4103810292729  
**Discount group:** D

#### technical data

length of discharge hose (m): 10  
connection discharge hose: G 1/4" male  
length of connecting hose (m): 1  
connection to connecting hose: G 1/4" female/female  
inner diameter of hose (DN): 6  
operating pressure max. (bar): 400  
colour  
casing: window grey, satin, RAL 7040  
arm: window grey, satin, RAL 7040  
supporting plate: window grey, satin, RAL 7040  
encasing: Pantone 294c, blue satin  
mounting bracket: Pantone 294c, blue satin  
dimensions LWH (mm): 495 x 158 x 508  
Weight (kg): 23,400

#### specification

- encased, for wall/floor mounting, outside swivel
- With hose stop

#### notes

- Pressol hose reels are exceedingly robust and are notable for their compact design.
- All metal parts are phosphatized, undercoated and painted.
- The high quality surface treatment of all steel parts ensures high corrosion resistance
- Axis (Ø 40 mm) of die cast parts. Dimensions selected by our engineers ensure almost unlimited life range
- The material combination axis / bearing and the spring unit are maintenance-free
- Easy assembly because the weight of the hose reel does not need to be supported while mounting.
- All swivel joints are ball bearing based
- High pressure in the supply system does not influence the power needed to rotate the drum.
- The hose can be engaged by rotating 1/4 turn.

#### packaging

dimensions LWH (mm): 540 x 580 x 160  
Weight (kg): 24,400  
Packing unit: 1.0