



One hand grease gun-EHFP

M 10 x 1-GRDR-MU

Item number: 12 250
EAN: 4103810122507
Discount group: A

Technical data

Grease gun connection, pressure-side: M 10 x 1
Filling nipple and ventilating valve: M 10 x 1
Capacity (cm³): 500
Refilling options: 400 g grease cartridge, DIN 1284, grease gun filling system or bulk grease
Diameter of grease piston (mm): 8
Grease pump piston actuation: manual, by means of pressure grip
Delivery rate/stroke (cm³): 0,8
Max. delivery pressure (bar): 260
Burst pressure system (bar): 850
Burst pressure grease gun head (bar): 1200
Operation of plunger rod: with L-design handle
Sealing cover: loose
Wall thickness of grease gun tube (mm): 1,0
Lacquering: silver
Dimensions LxWxH (mm): 405 x 400 x 66
Weight (kg): 1,20

Specification

- Spout, straight, M 10 x 1, 150 mm (12 435)
- Hydraulic coupler, M 10 x 1 female (12 631)
- Filling nipple (FN), M 10 x 1 male (12 670)
- Sales package, with Bar code

Notes

- Operates with greases up to NLGI grade 2 at 20°C
- plunger with exactly fitting when using bulk grease or cartridge
- Similar to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 40.000 actuating cycles
- Separate filling and ventilation valves on grease gun head
- Grease gun head, zinc die casting Z 410
- sure grip handling due to deep band knurls
- safe handle on the plunger rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm): 400 x 140 x 75
Weight (kg): 1,31
Packing unit: 1.0