



Pneumatic pump 1:1-brass

SRL 860-200/220 l container

Item number: 19 135 843
EAN:
Discount group: D

technical data

length suction tube: 860
Pressure ratio: 1:1
Max. diameter (mm): 130
Max. air pressure (bar): 10
Min. air pressure (bar): 2
recommended air pressure (bar): 8
cylinder capacity engine cm³: 220
cylinder capacity pump cm³: 220
quantity of strokes at 8 bar at a free-flow (min.): 240
pump capacity at 8 bar at a free-flow (l/min): 66
pump pressure at 8 bar air pressure (bar): 8
air consumption at 8 bar air pressure (l/min): 450
length of discharge pipe work: Depends on size of installation.
Max. suction height: 6 m, suction tube G 1"
compressed air connection: G 1/4" female
connection suction side: G 1" i
connection discharge side: G 3/4" a
connection container: G 2" male, drum adapter
Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A): 78
Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A): 77
classical liquids to be discharged: Cooling liquid, anti-freeze, windscreen washing liquid
colour: blue Pantone 294 c
material pump housing: brass
materials of parts in contact with liquid: steel, brass, FKM Viton®
length of engine (mm): 375
weight engine (kg): 4,300

specification

- for 200/220 l container
- Suction tube, G 1" male
- not calibratable
- To discharge low viscosity liquids, such as colling liquids, anti-freeze and wind-screen liquids

notes

- Operate pneumatic-pump with maintaining unit 20 218 950

packaging

dimensions LWH (mm): 1310 x 190 x 195
weight (kg): 9,200
Packing unit: 1.0