



NUMERIXx³-G 1" fem-G 1" fem

Val gear meter-mechanical

Item number: 23 192
EAN: 4048358231925
Discount group: D

Technical data

Distance in-/out flange (mm): 95
Connection on both ends: G 1" female
Pre-set flow direction: from left to right
Media: diesel, fuel oil, selflubricating low viscosity liquids
Flow capacity min. (l/min): 2
Flow capacity max. (l/min): 100
Permitted liquid temperature max. (°C): -10 up to +60
Permitted ambient temperature (°C): -10 up to +80
Measuring tolerance (%): +/- 1
Nominal pressure (bar): 3,5
Burst pressure (bar): 28
Materials of parts in contact with liquid
Meter housing: AISi 12 (sea water resistant)
oval gears: POM
Gear mechanism: ABS-plastic
Seals: NBR 70
External dimensions LWH (mm): 145x120x125
Weight (kg): 1,14

Specification

- Meter: daily meter with 3 digits, resettable, partition 100 ml
- Totalisator 6 digits, accounts in litres
- Totalisator re-starts after 999 999 l with zero

Notes

- Meter for various in-line installation

Packaging

Dimensions packaging LxWxH (mm): 150 x 135 x 135
Weight including package (kg): 1,27
Packing unit: 1.0