



Standard grease gun, HHFP
with ZBH, connection M 10 x 1

Item number: 12 634
EAN: 4103810126345
Discount group: A

technical data

grease gun connection,
pressure-side: M 10 x 1
capacity (cm³): 500 cm³
loading: 400 g grease cartridge, DIN 1284, or bulk grease
diameter of piston (mm): 8 mm
actuation grease piston: manually lever operated
Delivery rate/stroke (cm³): 1,2, at a counter-pressure of 400 bar
Discharge pressure (bar): up to 400 bar
burst pressure (system): 850 bar
burst pressure (grease gun head):
1200 bar
operation of plunger rod: with L-design handle
Sealing cover: loose
wall thickness of grease gun tube
(mm): 1,0 mm
colour: silver

specification

- With 1 spout, angled, M 10 x 1, 150 mm (12 635)
- With 1 coupler, 4 jaws, M 10 x 1
- Sales package, with Bar code

notes

- operates with greases up to NLGI grade 2.
- plunger with exactly fitting when using bulk grease or cartridge
- Acc. to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 5000 actuating cycles
- grease gun head, zinc die casting Z 410
- sure grip handling due to deep band knurls
- safe handle on the plunger rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

packaging

Dimensions LxWxH (mm): 400 x 140 x 75
Weight (kg): 1,35
Packing unit: 1.0