


Oil pump 10 l/min

230 V-1~AC-50 Hz-EUS



Item number: 23 337
EAN: 4048358233370
Discount group: D

Technical data

Connecting cable, length (m): 1,8
 Connection suction side: G 3/4" male thread (both sides)
 Connection discharge side: G 1/2" male

Hydraulic data

Pump design: gearwheel pump, selfpriming

Delivery rate under free discharge (l/min): 10

Suction height (m): 3,5

Discharge pressure up to (bar): 10

Flow media: oils up to SAE 90

Motor data

Voltage (V): 230

Frequency (Hz): 50

Power consumption (A): 5,5

Power (kW): 0,5

Thermal protection: self resetting

Duty cycle (min): Continuous operation – a real endurance runner

Torque (Nm): 2


Rotation speed (rpm): 1450

Type of construction: IMB 3

Safety class: IP54

Dimensions LxWxH (mm): 290 x 200 x 210

Weight (kg): 12,6



Specification

- On/Off switch
- Adjustable by-pass (pre-set at 7 bar)
- With venting valve
- Acc. to TRBF



Special notes

- Internal gear pump with corrugated filling part. This construction effects:
- Marginal inhomogeneous grade of volume flow rate
- Low noise level
- Compact construction
- The longer tooth engagement provides an improved seal effect and a better suction and discharge angle
- Optimal suction characteristics
- Pump for tank and wall mounting
- Pump is designed for use in conjunction with pipe lines up to 70 meters, depending on cross section of pipe line
- Recommended accessories for wall mounting:
- (19 512) and (19 522), (19 523), (19 523 001)



Packaging

Dimensions LxWxH (mm): 370 x 220 x 200

Weight (kg): 12,9

Packing unit: 1,0

