



# Lighting-fast filling G2" ROTARY PUMP

- Very compact design
- Complete sealing of the different components through the seals
- Assembly, operation & container change without any additional tools required
- Completely dismantlable - easy to clean
- 3 year warranty when using the supplied suction basket (excluding wear & tear parts)

Impact resistant pump housing

Painless hand-rotation operation

Non-slip handle

With suction filter against filth and dirt



**60 × 18 l/min**  
3.4 gal/min

Excellent suction performance due to high precision components



# G2" ROTARY PUMP



**Positioning of the spout to avoid any spills**



**Hose holder**  
with 13 056

Packaging  
Packing unit: 1,0  
Dimensions LxWxH (mm): 390 x 120 x 240  
Weight including package (kg): 2,85



## SPECIFICATIONS

- Telescopic suction tube (13 094) adjustable in length (from 355 to 955 mm)
- Barrel screw adapter G 2" (13 097 002)
- With suction filter against filth and dirt (04 464)

### 13 055

With delivery spout

### 13 056

With 2 m delivery hose and spout,  
with steel delivery spout (13 044 020) and hose holder

## TECHNICAL SPECIFICATIONS

<b>Delivery rate (l/rotation)</b>	0,3
<b>Delivery rate at 60 rotations/min</b>	18 l/min - 3.4 gal/min (Diesel)
<b>Pumping media</b>	Oils, up to SAE 90, self-lubricating, non-aggressive media, fuel oil, diesel, petroleum
<b>Usage</b>	For 60 / 200 / 220 l containers
<b>Application</b>	For filling measuring vessels, storage cans and canisters
<b>Length three-part suction pipe</b>	355 - 955 mm / 14" - 38.5 "
<b>Drum adapter</b>	G 2" male