TECHNICAL EXCELLENCE. SINCE 1929.

HOSE REELS

SERIE 805

ART. 805/8/S

Hose length (m)
16

Hose internal diameter (mm)
8 mm (5/16")

Tube type
KPU

Maximum pressure
15 bar




ISO EN 12100 | 2006/42/CE | CE | TÜVNORD Baumuster geprüft | 14 | mm 550x505x270

TECHNICAL DATA

Article	Hose internal diameter (mm)	Hose length (m)	Cut length (m)	Maximum pressure	End fitting	Temperature	Incoming connection	Tube type	Color	Tube colour	Fluid type
805/8/S	8 mm (5/16")	16	1.5	15 bar	1/4" M BSP	-5 °C/+50 °C	NO	KPU	Silver	BLUE	Air - Water

Please note: The images are for illustrative and explanatory purposes only

OVERALL DIMENSIONS



Technical features

- Available with KPU and FLEX hose.
- Technopolymer structure.
- Leda spotlight
- Automatic device to stop the tube at the desired length, which can be disconnected if necessary.
- Available in yellow or silver gray color.

Please note: The images are for illustrative and explanatory purposes only


OPTIONAL ACCESSORIES AND SPARE PARTS

ART. 805/SR

Safety Return

Safety Return allows the slow rewinding of the cable avoiding dangerous repercussions in case the cable gets out of hand to the operator.





ART. 949/805-7000

Dispositivo antirotazione

Dispositivo opzionale per rendere fisso, anziché orientabile l'avvolgitubo. Indispensabile per l'applicazione a soffitto.