



ltem number: EAN: Discount group: Availability:	12 986 4103810129865 A as of the end of September 2014
·	·
Technical data	
Capacity (ml):	750
Suction volume (%):	100
Diameter tubing outside (mm):	60
Tube thickness (mm):	3
Stroke length (mm):	400 12
Suction hose diameter (mm):	600
Suction hose length (mm): Discharge hose diameter (mm):	16
Length of discharge hose (mm):	600
Length of discharge hose (min).	000
Materials of parts in contact with liquid	
Head and cover:	PAGF 30 (PP glass-fibre reinforced)
Tube:	PVC
Piston:	FKM (Viton®)
Piston rod:	stainless steel
Valves / connection:	aluminium
Valve ball:	PTFE
Suction hose:	PVC
Discharge hose:	PVC
Dimensions LxWxH (mm):	95 x 65 x 450
Weight (kg):	0,6

Specification

- Ergonomic T-grip
- Suction hose (12 997)
- Discharge hose (12 998)

Notes

- For mineral, synthetic and biological oils, diesel, heating oil, antifreeze (window and motor), glycerin, urea up to 10%, water and seawater
- The plunger ensures reliable suction of the liquid
- · All materials that come into contact with the media are of high quality

Packaging

Weight including package (kg):	0,8
Packing unit:	1.0