



ROTAxx 38 l/min-12 V-DC
ZVPP-ABK-EBZM

Item number: 23 912
EAN: 4103810239120
Discount group: D

technical data

connecting cable with battery
terminal clips, length (m): 2
connection container: G 2" male, drum adapter
Connection discharge side: G 1" male
Hydraulic data
Pump design: vane pump, selfpriming
flow rate: 38 l/min, free discharge
Discharge pressure (bar): 1,1
Suction height (m): 2
flow media: Fuel oil and diesel
Motor data
Voltage (V): 12
locking device (A): 25
Power consumption (A): 22
Power (kW): 0,26
Duty cycle (min): 30
Torque (Nm): 0,4
Speed (rpm): 2900
Type of construction: IMB 5
Protection class: IP 54
material of pump housing and pump: GG / stainless steel
Dimensions LxWxH (mm): 202 x 325 x 138
Weight (kg): 7

specification

- For 200 up to 1000 l container
- Barrel screw coupling, G 2" male
- vane pump, with integral bypass
- On/Off switch
- siphon protection acc. to WHG (German government regulation for environmental care), continuously active
- discharge hose 4 m, DN 19, G 1" male, G 1" female (23 155 957)
- Polypropylene nozzle valve, ZVPP (23161)
- In-line meter NUMERlxx³, three digits (23 193)
- Suction hose, 1,6 m, G 1" male, G 1" female, DN 25 (23 156)
- Foot valve with filter (19 890)
- valuable sales package

packaging

Dimensions LxWxH (mm): 350 x 350 x 300
Weight (kg): 14
Packing unit: 1.0