



ltem number:	14 400 211
EAN:	4103810704000
Discount group:	A
<b>Technical data</b>	M 10 x 1
Grease gun connection, pressure-side:	M 10 x 1
Filling nipple:	500
Capacity (cm <sup>3</sup> ):	400 g grease cartridge, DIN 1284, grease gun
Refilling options:	filling system or bulk grease
Grease pump piston actuation:	manual, by means of pressure grip
Calibration Volume Delivery rate/stroke (cm³): Max. delivery pressure (bar):	1,1 200
Calibration Pressure Delivery rate/stroke (cm³): Max. delivery pressure (bar):	0,7 300
Grease gun tube colour:	black
Dimensions LxWxH (mm):	400 x 165 x 66
Weight (kg):	1,3

## Specification

• Filling nipple (FN), M 10 x 1 male (12 670)

One hand grease gun 2014.1 M 10 x 1

FN-black-without ZBH

- Galvanized parts: grip, lever, pulling strap, safety catch, cap, push rod
- Grease gun head, zinc die casting Z 410
- Dismantleable and movable push rod system
- T-grip, optimized grip and pressure optimized
- Ergonomic handle, non-slip, excellent power transfer and handling
- Packed in single carton box
- Grease gun also available in the colors silver, red, blue, green and yellow

## Special notes

- The construction allows a single hand operated lubrication for an easy work in restricted areas
- Can be switched with the hand grip from grease delivery with high volume to high pressure
- Due to the flexibility of the push rod, the plunger can be inserted into damaged cartridges or cartridges not exactly matching the standard dimensions
- Damaged cartridges can easily be removed
- Push rod can be locked in any position push rod does not have to be fully retracted to release the spring pressure on the grease (grease does not saponify)
- The ease of dismantling permits simple cleaning
- Rolled thread on the grease gun tube resists damage from impact and allows quick and easy screwing-in by 1,5 turns
- High-speed ventilation, by half a rotation of the grease gun tube
- Designed for use in rough conditions
- Similar to DIN 1283

## Packaging

Dimensions LxWxH (mm): Weight including package (kg): Packing unit: 400 x 165 x 75 1,45 1,0