



One hand grease gun-EHFP

125 cm³-M 10 x 1-GRDR-MU

Item number: 12 226
EAN: 4103810122262
Discount group: A

Technical data

Grease gun connection, pressure-side: M 10 x 1
Filling nipple and ventilating valve: M 10 x 1
Capacity (cm³): 125
Refilling options: grease gun filling system or bulk grease
Diameter of grease piston (mm): 8
Grease pump piston actuation: manual, by means of pressure grip
Delivery rate/stroke (cm³): 0,4
Discharge pressure up to (bar): 550
Burst pressure system (bar): 850
Burst pressure grease gun head (bar): 1200
Operation of plunger rod: with L-design handle
Sealing cover: loose
Wall thickness of grease gun tube (mm): 1,0
Lacquering: silver

Specification

- With 1 spout, straight, M 10 x 1, 150 mm
- With 1 coupler, 4 jaws, M 10 x 1 (12 643)
- Sales package, with Bar code

Notes

- Operates with greases up to NLGI grade 2.
- Contoured plunger, tight fitting, with bulk grease
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 5000 actuating cycles
- Separate filling and ventilation valves on grease gun head
- Grease gun head, zinc die casting Z 410
- safe handle on the plunger rod
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease
- High-speed ventilation, by half a rotation of the grease gun tube

Packaging

Dimensions LxWxH (mm): 285 x 120 x 55
Weight (kg): 0,66
Packing unit: 1.0