



Grease gun-G 1/8" fem-EBZD

high pressure hose-coupler

Item number: 18 102 950
EAN: 4103810424960
Discount group: D

Technical data

Connection 1: G 1/8" i
Connection 2: coupler, for hydraulic grease nipples, DIN 71412
Operating pressure max. (bar): 400
Application range: NLGI 0 up to NLGI 3
Operating temperature (°C): -10 / +60
Weight (kg): 1,32

Specification

- Grease meter (18 115), 5 digits, display of partial quantity and totalisator, resettable
- Reinforced hose with precision machined coupler (12 755 814)
- Connector G 1/8" – meter/grease gun with nut (92 459)
- Z-swivel joint (18 082)
- Packed in carton box
- With EAN bar code

Special notes

- Gun body, guard and trigger made of impact and pressure resistant die cast zinc
- Galvanically surface-treated die cast zinc parts
- Low release force at high pressures
- No pressure surge during opening
- Large size hanging bracket
- Ergonomic component design
- Suitable for greases NLGI 0 up to NLGI 3
- Completely dismountable - easy to clean
- Guard for trigger lock
- Spare parts available for 10 years

Packaging

Dimensions LxWxH (mm): 270 x 170 x 130
Weight including package (kg): 1,42
Packing unit: 1,0